

**International Window 5420 3/4" Insulating Glass Unit Performance**

Side Load Single Hung w/Steel Spacer	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured & SDL Grid	Sculptured Grid with Argon	1/8" x 3/4" Grid	1/8" x 3/4" Grid with Argon		Sculptured Grid	1/8" x 3/4" Grid		Sculptured Grid	1/8" x 3/4" Grid
SS clear/ SS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.61	0.49	0.55	0.64	0.50	0.57
DS clear/ DS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.59	0.47	0.53	0.63	0.50	0.56
3/16 clear/ 3/16 clear	0.50	0.48	0.52	0.50	0.52	0.50	0.56	0.45	0.50	0.62	0.49	0.55
SS EnergyShield™/ SS clear	0.35	0.32	0.35	0.32	0.35	0.32	0.31	0.25	0.28	0.56	0.45	0.50
DS EnergyShield™/ DS clear	0.35	0.32	0.35	0.32	0.35	0.32	0.30	0.25	0.27	0.56	0.44	0.50
3/16 EnergyShield™/ 3/16 clear	0.37	0.33	0.40	0.37	0.40	0.37	0.30	0.25	0.27	0.55	0.43	0.49
SS EnergyShield Xtreme™/ SS clear	0.35	0.31	0.35	0.31	0.35	0.31	0.22	0.18	0.20	0.50	0.40	0.45
DS EnergyShield Xtreme™/ DS clear	0.35	0.31	0.35	0.31	0.35	0.31	0.22	0.18	0.20	0.50	0.39	0.44
3/16 EnergyShield Xtreme™/ 3/16 clear	0.37	0.32	0.40	0.36	0.40	0.36	0.22	0.18	0.20	0.49	0.38	0.43
DS bronze/ DS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.48	0.39	0.43	0.47	0.37	0.42
3/16 bronze/ 3/16 clear	0.50	0.48	0.52	0.50	0.52	0.50	0.43	0.35	0.39	0.40	0.32	0.36
3/16 Solarcool/ 3/16 clear	0.50	0.48	0.52	0.50	0.52	0.50	0.26	0.21	0.24	0.16	0.12	0.14
DS grey/ DS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.45	0.36	0.40	0.42	0.33	0.38
3/16 grey/ 3/16 clear	0.50	0.48	0.52	0.50	0.52	0.50	0.39	0.32	0.35	0.35	0.28	0.31
DS greylite # 31/ DS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.25	0.20	0.23	0.17	0.13	0.15
DS Azuria/ DS clear	0.48	0.47	0.48	0.47	0.48	0.47	0.38	0.30	0.34	0.54	0.42	0.48
3/16 Azuria/ 3/16 clear	0.50	0.48	0.52	0.50	0.52	0.50	0.33	0.27	0.30	0.50	0.39	0.44
DS bronze/ DS EnergyShield™	0.35	0.32	0.35	0.32	0.35	0.32	0.29	0.24	0.26	0.41	0.33	0.37
3/16 bronze/ 3/16 EnergyShield™	0.37	0.33	0.40	0.37	0.40	0.37	0.27	0.22	0.24	0.36	0.28	0.32
DS grey/ DS EnergyShield™	0.35	0.32	0.35	0.32	0.35	0.32	0.27	0.22	0.25	0.37	0.29	0.33
3/16 grey/ 3/16 EnergyShield™	0.37	0.33	0.40	0.37	0.40	0.37	0.25	0.20	0.22	0.31	0.24	0.28
DS Azuria/ DS EnergyShield™	0.35	0.32	0.35	0.32	0.35	0.32	0.28	0.23	0.26	0.48	0.38	0.43
3/16 Azuria/ 3/16 EnergyShield™	0.37	0.33	0.40	0.37	0.40	0.37	0.27	0.22	0.24	0.44	0.35	0.39
3/16 Solexia/ 3/16 EnergyShield™	0.37	0.33	0.40	0.37	0.40	0.37	0.30	0.24	0.27	0.49	0.39	0.44

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>\*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024

**International Window 5420 3/4" Insulating Glass Unit Performance**

**Side Load Single Hung  
w/Xtreme Spacer**

	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured & SDL Grid	Sculptured & SDL Grid with Argon	1/8" x 3/4" Grid	1/8" x 3/4" Grid with Argon		Sculptured & SDL Grid	1/8" x 3/4" Grid		Sculptured & SDL Grid	1/8" x 3/4" Grid
SS clear/ SS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.61	0.49	0.55	0.64	0.50	0.57
DS clear/ DS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.59	0.47	0.53	0.63	0.50	0.56
3/16 clear/ 3/16 clear	0.49	0.46	0.51	0.49	0.51	0.49	0.56	0.45	0.50	0.62	0.49	0.55
SS EnergyShield™/ SS clear	0.34	0.30	0.34	0.30	0.34	0.30	0.31	0.25	0.28	0.56	0.45	0.50
DS EnergyShield™/ DS clear	0.34	0.30	0.34	0.30	0.34	0.30	0.30	0.25	0.27	0.56	0.44	0.50
3/16 EnergyShield™/ 3/16 clear	0.36	0.31	0.39	0.35	0.39	0.35	0.30	0.25	0.27	0.55	0.43	0.49
SS EnergyShield Xtreme™/ SS clear	0.33	0.30	0.33	0.30	0.33	0.30	0.22	0.18	0.20	0.50	0.40	0.45
DS EnergyShield Xtreme™/ DS clear	0.33	0.30	0.33	0.30	0.33	0.30	0.22	0.18	0.20	0.50	0.39	0.44
3/16 EnergyShield Xtreme™/ 3/16 clear	0.35	0.31	0.38	0.34	0.38	0.34	0.22	0.18	0.20	0.49	0.38	0.43
DS bronze/ DS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.48	0.39	0.43	0.47	0.37	0.42
3/16 bronze/ 3/16 clear	0.49	0.46	0.51	0.49	0.51	0.49	0.43	0.35	0.39	0.40	0.32	0.36
3/16 Solarcool/ 3/16 clear	0.49	0.46	0.51	0.49	0.51	0.49	0.26	0.21	0.24	0.16	0.12	0.14
DS grey/ DS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.45	0.36	0.40	0.42	0.33	0.38
3/16 grey/ 3/16 clear	0.49	0.46	0.51	0.49	0.51	0.49	0.39	0.32	0.35	0.35	0.28	0.31
DS greylite # 31/ DS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.25	0.20	0.23	0.17	0.13	0.15
DS Azuria/ DS clear	0.47	0.45	0.47	0.45	0.47	0.45	0.38	0.30	0.34	0.54	0.42	0.48
3/16 Azuria/ 3/16 clear	0.49	0.46	0.51	0.49	0.51	0.49	0.33	0.27	0.30	0.50	0.39	0.44
DS bronze/ DS EnergyShield™	0.34	0.30	0.34	0.30	0.34	0.30	0.29	0.24	0.26	0.41	0.33	0.37
3/16 bronze/ 3/16 EnergyShield™	0.36	0.31	0.39	0.35	0.39	0.35	0.27	0.22	0.24	0.36	0.28	0.32
DS grey/ DS EnergyShield™	0.34	0.30	0.34	0.30	0.34	0.30	0.27	0.22	0.25	0.37	0.29	0.33
3/16 grey/ 3/16 EnergyShield™	0.36	0.31	0.39	0.35	0.39	0.35	0.25	0.20	0.22	0.31	0.24	0.28
DS Azuria/ DS EnergyShield™	0.34	0.30	0.34	0.30	0.34	0.30	0.28	0.23	0.26	0.48	0.38	0.43
3/16 Azuria/ 3/16 EnergyShield™	0.36	0.31	0.39	0.35	0.39	0.35	0.27	0.22	0.24	0.44	0.35	0.39
3/16 Solexia/ 3/16 EnergyShield™	0.36	0.31	0.39	0.35	0.39	0.35	0.30	0.24	0.27	0.49	0.39	0.44

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>\*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024

**International Window 5420 I 1/8" Triple Glaze Unit Performance**

**Side Load Single Hung  
w/Steel Spacer**

	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured & SDL Grid	Sculptured & SDL Grid with Argon	1/8" x 3/4" Grid	1/8" x 3/4" Grid with Argon		Sculptured & SDL Grid	1/8" x 3/4" Grid		Sculptured & SDL Grid	1/8" x 3/4" Grid
SS clear/ SS clear / SS clear	0.37	0.35	0.37	0.35	0.37	0.35	0.55	0.44	0.49	0.58	0.46	0.52
DS clear/ DS clear / DS clear	0.37	0.35	0.38	0.36	0.38	0.36	0.53	0.42	0.47	0.57	0.45	0.51
3/16 clear/ 3/16 clear / 3/16 clear	0.40	0.37	0.40	0.37	0.40	0.37	0.50	0.40	0.45	0.56	0.44	0.50
SS EnergyShield™/ SS clear / SS clear	0.30	0.27	0.30	0.28	0.30	0.28	0.28	0.23	0.26	0.52	0.41	0.46
DS EnergyShield™/ DS clear / DS clear	0.30	0.28	0.32	0.30	0.32	0.30	0.28	0.23	0.25	0.51	0.40	0.45
3/16 EnergyShield™/ 3/16 clear / 3/16 clear	0.34	0.30	0.35	0.31	0.35	0.31	0.28	0.23	0.25	0.50	0.39	0.44
SS EnergyShield™/ SS clear / SS EnergyShield™	0.25	0.23	0.26	0.24	0.26	0.24	0.26	0.21	0.24	0.46	0.36	0.41
DS EnergyShield™/ DS clear / DS EnergyShield™	0.27	0.24	0.27	0.26	0.27	0.26	0.26	0.21	0.24	0.45	0.35	0.40
3/16 EnergyShield™/ 3/16 clear / 3/16 EnergyShield™	0.30	0.27	0.30	0.28	0.30	0.28	0.26	0.21	0.23	0.44	0.35	0.39
SS EnergyShield Xtreme™/ SS clear / SS clear	0.30	0.27	0.30	0.28	0.30	0.28	0.20	0.16	0.18	0.46	0.36	0.41
DS EnergyShield Xtreme™/ DS clear / DS clear	0.31	0.28	0.32	0.30	0.32	0.30	0.20	0.17	0.18	0.45	0.36	0.40
3/16 EnergyShield Xtreme™/ 3/16 clear / 3/16 clear	0.34	0.30	0.35	0.31	0.35	0.31	0.20	0.17	0.19	0.44	0.35	0.39
SS EnergyShield Xtreme™/ SS clear / SS EnergyShield Xtreme™	0.25	0.23	0.25	0.24	0.25	0.24	0.20	0.16	0.18	0.46	0.36	0.41
DS EnergyShield Xtreme™/ DS clear / DS EnergyShield Xtreme™	0.27	0.23	0.27	0.24	0.27	0.24	0.20	0.17	0.18	0.45	0.36	0.40
3/16 EnergyShield Xtreme™/ 3/16 clear / 3/16 EnergyShield Xtreme™	0.30	0.26	0.30	0.27	0.30	0.27	0.20	0.17	0.19	0.44	0.35	0.39

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024

**International Window 5420 I 1/8" Triple Glaze Unit Performance**

**Side Load Single Hung  
w/Xtreme Spacer**

	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured & SDL Grid	Sculptured & SDL Grid with Argon	1/8" x 3/4" Grid	1/8" x 3/4" Grid with Argon		Sculptured & SDL Grid	1/8" x 3/4" Grid		Sculptured & SDL Grid	1/8" x 3/4" Grid
SS clear/ SS clear / SS clear	0.35	0.33	0.35	0.33	0.35	0.33	0.55	0.44	0.49	0.58	0.46	0.52
DS clear/ DS clear / DS clear	0.36	0.34	0.36	0.35	0.36	0.35	0.53	0.42	0.47	0.57	0.45	0.51
3/16 clear/ 3/16 clear / 3/16 clear	0.38	0.36	0.38	0.36	0.38	0.36	0.50	0.40	0.45	0.56	0.44	0.50
SS EnergyShield™/ SS clear / SS clear	0.28	0.25	0.29	0.26	0.29	0.26	0.28	0.23	0.26	0.52	0.41	0.46
DS EnergyShield™/ DS clear / DS clear	0.28	0.26	0.31	0.28	0.31	0.28	0.28	0.23	0.25	0.51	0.40	0.45
3/16 EnergyShield™/ 3/16 clear / 3/16 clear	0.32	0.29	0.33	0.30	0.33	0.30	0.28	0.23	0.25	0.50	0.39	0.44
SS EnergyShield™/ SS clear / SS EnergyShield™	0.23	0.21	0.24	0.22	0.24	0.22	0.26	0.21	0.24	0.46	0.36	0.41
DS EnergyShield™/ DS clear / DS EnergyShield™	0.25	0.22	0.26	0.24	0.26	0.24	0.26	0.21	0.24	0.45	0.35	0.40
3/16 EnergyShield™/ 3/16 clear / 3/16 EnergyShield™	0.29	0.25	0.29	0.27	0.29	0.27	0.26	0.21	0.23	0.44	0.35	0.39
SS EnergyShield Xtreme™/ SS clear / SS clear	0.28	0.25	0.28	0.26	0.28	0.26	0.20	0.16	0.18	0.46	0.36	0.41
DS EnergyShield Xtreme™/ DS clear / DS clear	0.29	0.26	0.31	0.28	0.31	0.28	0.20	0.17	0.18	0.45	0.36	0.40
3/16 EnergyShield Xtreme™/ 3/16 clear / 3/16 clear	0.32	0.29	0.33	0.30	0.33	0.30	0.20	0.17	0.19	0.44	0.35	0.39
SS EnergyShield Xtreme™/ SS clear / SS EnergyShield Xtreme™	0.23	0.20	0.23	0.22	0.23	0.22	0.20	0.16	0.18	0.46	0.36	0.41
DS EnergyShield Xtreme™/ DS clear / DS EnergyShield Xtreme™	0.25	0.21	0.25	0.22	0.25	0.22	0.20	0.17	0.18	0.45	0.36	0.40
3/16 EnergyShield Xtreme™/ 3/16 clear / 3/16 EnergyShield Xtreme™	0.28	0.24	0.29	0.25	0.29	0.25	0.20	0.17	0.19	0.44	0.35	0.39

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024