

| International Window 8220 3/4" Insulating Glass Unit Performance | | | | | | | | | | | | |
|---|--------------------|------------|-----------------|----------------------------|------------------|-----------------------------|-------------|-----------------|------------------|----------------------|-----------------|------------------|
| Horizontal Slider w/Steel Spacer | U-Factors | | | | | | SHGC | | | Visible Light | | |
| | Air fill | With Argon | Sculptured Grid | Sculptured Grid with Argon | 1/8" x 3/4" Grid | 1/8" x 3/4" Grid with Argon | | Sculptured Grid | 1/8" x 3/4" Grid | | Sculptured Grid | 1/8" x 3/4" Grid |
| | SS clear/ SS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.67 | 0.54 | 0.60 | 0.70 | 0.56 |
| DS clear/ DS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.65 | 0.52 | 0.58 | 0.69 | 0.55 | 0.62 |
| 3/16 clear/ 3/16 clear | 0.58 | 0.55 | 0.61 | 0.58 | 0.61 | 0.58 | 0.62 | 0.50 | 0.56 | 0.68 | 0.54 | 0.61 |
| SS EnergyShield™/ SS clear | 0.41 | 0.38 | 0.43 | 0.39 | 0.41 | 0.38 | 0.33 | 0.27 | 0.30 | 0.60 | 0.48 | 0.54 |
| DS EnergyShield™/ DS clear | 0.42 | 0.37 | 0.44 | 0.39 | 0.42 | 0.37 | 0.33 | 0.27 | 0.30 | 0.59 | 0.47 | 0.53 |
| 3/16 EnergyShield™/ 3/16 clear | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.33 | 0.27 | 0.30 | 0.58 | 0.47 | 0.52 |
| SS EnergyShield Xtreme™/ SS clear | 0.41 | 0.37 | 0.42 | 0.38 | 0.41 | 0.37 | 0.25 | 0.20 | 0.22 | 0.53 | 0.42 | 0.47 |
| DS EnergyShield Xtreme™/ DS clear | 0.41 | 0.37 | 0.43 | 0.39 | 0.41 | 0.37 | 0.25 | 0.20 | 0.22 | 0.52 | 0.42 | 0.47 |
| 3/16 EnergyShield Xtreme™/ 3/16 clear | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.25 | 0.21 | 0.23 | 0.52 | 0.41 | 0.46 |
| DS bronze/ DS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.53 | 0.43 | 0.48 | 0.51 | 0.41 | 0.46 |
| 3/16 bronze/ 3/16 clear | 0.58 | 0.55 | 0.61 | 0.58 | 0.61 | 0.58 | 0.48 | 0.39 | 0.43 | 0.44 | 0.35 | 0.40 |
| 1/4 Solarcool/ DS clear | 0.57 | 0.55 | 0.65 | 0.56 | 0.59 | 0.56 | 0.28 | 0.23 | 0.25 | 0.16 | 0.13 | 0.14 |
| DS grey/ DS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.50 | 0.40 | 0.45 | 0.46 | 0.37 | 0.41 |
| 3/16 grey/ 3/16 clear | 0.58 | 0.55 | 0.61 | 0.58 | 0.61 | 0.58 | 0.44 | 0.35 | 0.39 | 0.38 | 0.31 | 0.34 |
| DS greylite # 31/ DS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.28 | 0.23 | 0.25 | 0.18 | 0.15 | 0.16 |
| DS Azuria/ DS clear | 0.56 | 0.54 | 0.57 | 0.54 | 0.56 | 0.54 | 0.42 | 0.34 | 0.38 | 0.59 | 0.47 | 0.53 |
| 3/16 Azuria/ DS clear | 0.56 | 0.54 | 0.58 | 0.55 | 0.56 | 0.54 | 0.37 | 0.30 | 0.33 | 0.55 | 0.44 | 0.49 |
| DS bronze/ DS EnergyShield™ | 0.42 | 0.37 | 0.44 | 0.39 | 0.42 | 0.37 | 0.33 | 0.27 | 0.30 | 0.44 | 0.35 | 0.39 |
| 3/16 bronze/ 3/16 EnergyShield™ | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.30 | 0.25 | 0.28 | 0.38 | 0.30 | 0.34 |
| DS bronze/ DS EnergyShield Xtreme™ | 0.41 | 0.37 | 0.43 | 0.39 | 0.41 | 0.37 | 0.29 | 0.24 | 0.26 | 0.39 | 0.31 | 0.35 |
| 3/16 bronze/ 3/16 EnergyShield Xtreme™ | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.26 | 0.22 | 0.24 | 0.34 | 0.27 | 0.30 |
| DS grey/ DS EnergyShield™ | 0.42 | 0.37 | 0.44 | 0.39 | 0.42 | 0.37 | 0.31 | 0.25 | 0.28 | 0.40 | 0.32 | 0.36 |
| 3/16 grey/ 3/16 EnergyShield™ | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.28 | 0.23 | 0.25 | 0.33 | 0.26 | 0.30 |
| DS Azuria/ DS EnergyShield™ | 0.42 | 0.37 | 0.44 | 0.39 | 0.42 | 0.37 | 0.32 | 0.26 | 0.29 | 0.51 | 0.41 | 0.46 |
| 3/16 Azuria/ 3/16 EnergyShield™ | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.30 | 0.24 | 0.27 | 0.47 | 0.37 | 0.42 |
| 3/16 Solexia/ 3/16 EnergyShield™ | 0.44 | 0.39 | 0.49 | 0.44 | 0.49 | 0.44 | 0.34 | 0.28 | 0.31 | 0.52 | 0.42 | 0.47 |
| DS EnergyShield Xtreme™/ DS ILE | 0.37 | 0.33 | 0.38 | 0.34 | 0.37 | 0.33 | 0.24 | 0.20 | 0.22 | 0.51 | 0.41 | 0.46 |
| 3/16 EnergyShield Xtreme™/ 3/16 ILE | 0.38 | 0.35 | 0.41 | 0.38 | 0.41 | 0.38 | 0.24 | 0.20 | 0.22 | 0.50 | 0.40 | 0.45 |

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.* ft²*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024

| International Window 8220 3/4" Insulating Glass Unit Performance | | | | | | | | | | | | |
|---|------------------|------------|-----------------|----------------------------|------------------|-----------------------------|-------------|-----------------|------------------|----------------------|-----------------|------------------|
| Horizontal Slider w/Xtreme Spacer | U-Factors | | | | | | SHGC | | | Visible Light | | |
| | Air fill | With Argon | Sculptured Grid | Sculptured Grid with Argon | 1/8" x 3/4" Grid | 1/8" x 3/4" Grid with Argon | | Sculptured Grid | 1/8" x 3/4" Grid | | Sculptured Grid | 1/8" x 3/4" Grid |
| | | | | Argon | Argon | Argon | | | | | Argon | Argon |
| SS clear/ SS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.67 | 0.54 | 0.60 | 0.70 | 0.56 | 0.63 |
| DS clear/ DS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.65 | 0.52 | 0.58 | 0.69 | 0.55 | 0.62 |
| 3/16 clear/ 3/16 clear | 0.57 | 0.54 | 0.60 | 0.57 | 0.60 | 0.57 | 0.62 | 0.50 | 0.56 | 0.68 | 0.54 | 0.61 |
| SS EnergyShield™/ SS clear | 0.40 | 0.36 | 0.41 | 0.37 | 0.40 | 0.36 | 0.33 | 0.27 | 0.30 | 0.60 | 0.48 | 0.54 |
| DS EnergyShield™/ DS clear | 0.40 | 0.36 | 0.43 | 0.38 | 0.40 | 0.36 | 0.33 | 0.27 | 0.30 | 0.59 | 0.47 | 0.53 |
| 3/16 EnergyShield™/ 3/16 clear | 0.43 | 0.38 | 0.48 | 0.43 | 0.48 | 0.43 | 0.33 | 0.27 | 0.30 | 0.58 | 0.47 | 0.52 |
| SS EnergyShield Xtreme™/ SS clear | 0.40 | 0.36 | 0.41 | 0.37 | 0.40 | 0.36 | 0.25 | 0.20 | 0.22 | 0.53 | 0.42 | 0.47 |
| DS EnergyShield Xtreme™/ DS clear | 0.40 | 0.36 | 0.41 | 0.37 | 0.40 | 0.36 | 0.25 | 0.20 | 0.22 | 0.52 | 0.42 | 0.47 |
| 3/16 EnergyShield Xtreme™/ 3/16 clear | 0.43 | 0.38 | 0.48 | 0.43 | 0.48 | 0.43 | 0.25 | 0.21 | 0.23 | 0.52 | 0.41 | 0.46 |
| DS bronze/ DS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.53 | 0.43 | 0.48 | 0.51 | 0.41 | 0.46 |
| 3/16 bronze/ 3/16 clear | 0.57 | 0.54 | 0.60 | 0.57 | 0.60 | 0.57 | 0.48 | 0.39 | 0.43 | 0.44 | 0.35 | 0.40 |
| 1/4 Solarcool/ DS clear | 0.56 | 0.54 | 0.64 | 0.55 | 0.58 | 0.55 | 0.28 | 0.23 | 0.25 | 0.16 | 0.13 | 0.14 |
| DS grey/ DS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.50 | 0.40 | 0.45 | 0.46 | 0.37 | 0.41 |
| 3/16 grey/ 3/16 clear | 0.57 | 0.54 | 0.60 | 0.57 | 0.60 | 0.57 | 0.44 | 0.35 | 0.39 | 0.38 | 0.31 | 0.34 |
| DS greylite # 31/ DS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.28 | 0.23 | 0.25 | 0.18 | 0.15 | 0.16 |
| DS Azuria/ DS clear | 0.55 | 0.53 | 0.56 | 0.53 | 0.55 | 0.53 | 0.42 | 0.34 | 0.38 | 0.59 | 0.47 | 0.53 |
| 3/16 Azuria/ DS clear | 0.56 | 0.53 | 0.57 | 0.54 | 0.56 | 0.53 | 0.37 | 0.30 | 0.33 | 0.55 | 0.44 | 0.49 |
| DS bronze/ DS EnergyShield™ | 0.40 | 0.36 | 0.43 | 0.38 | 0.40 | 0.36 | 0.33 | 0.27 | 0.30 | 0.44 | 0.35 | 0.39 |
| 3/16 bronze/ 3/16 EnergyShield™ | 0.43 | 0.38 | 0.48 | 0.43 | 0.48 | 0.43 | 0.30 | 0.25 | 0.28 | 0.38 | 0.30 | 0.34 |
| DS grey/ DS EnergyShield™ | 0.40 | 0.36 | 0.43 | 0.38 | 0.40 | 0.36 | 0.31 | 0.25 | 0.28 | 0.40 | 0.32 | 0.36 |
| 3/16 grey/ 3/16 EnergyShield™ | 0.43 | 0.38 | 0.48 | 0.43 | 0.48 | 0.43 | 0.28 | 0.23 | 0.25 | 0.33 | 0.26 | 0.30 |
| DS Azuria/ DS EnergyShield™ | 0.40 | 0.36 | 0.43 | 0.38 | 0.40 | 0.36 | 0.32 | 0.26 | 0.29 | 0.51 | 0.41 | 0.46 |
| 3/16 Azuria/ 3/16 EnergyShield™ | 0.43 | 0.38 | 0.48 | 0.43 | 0.48 | 0.43 | 0.30 | 0.24 | 0.27 | 0.47 | 0.37 | 0.42 |
| 3/16 Solexia/ DS EnergyShield™ | 0.41 | 0.36 | 0.43 | 0.39 | 0.41 | 0.36 | 0.34 | 0.27 | 0.30 | 0.52 | 0.42 | 0.47 |
| DS EnergyShield Xtreme™/ DS ILE | 0.35 | 0.32 | 0.37 | 0.33 | 0.35 | 0.32 | 0.24 | 0.20 | 0.22 | 0.51 | 0.41 | 0.46 |
| DS EnergyShield Xtreme™/ 3/16 ILE | 0.35 | 0.32 | 0.37 | 0.33 | 0.35 | 0.32 | 0.24 | 0.20 | 0.22 | 0.51 | 0.40 | 0.45 |

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.*ft²*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost
 EnergyShield™ spectrally selective Low-E with emissivity 0.036
 EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024